



Date: _____
Time: _____
Installer: _____

Installation Checklist for Insane Audio Head Units

Shipping screws have been removed from the top of the unit (JK1001 and FJ1001 only)

GPS antenna is plugged into the correct port

Port should be labeled, but that this varies based on product. Check install manual.

WiFi antenna is plugged into the correct port

Port should be labeled, but that this varies based on product. Check install manual.

USB extension cord and iPod cable are both wired to the glove box

For I/E JK1001 and I/E JK2001, AM/FM pigtail is connected to the rear of the unit and plugged into the WHITE OEM antenna cable (NOT the yellow one)

Wiring harness is plugged into the Insane Audio head unit and the OEM wiring harness. All connections are snug.

Note that the connection at the rear of our unit is intentionally a tight fit to help keep moisture out. Verify no pins are bent, plug straight and all the way in.

External mic is connected to the rear of the unit and wired to your desired location

We recommend putting it on the steering column, as far away from gauges as possible and as close to passenger as possible.

All additional accessories are connected properly

InsaneTV, rearview camera, rock camera, etc

Blue OBDII adapter is plugged into vehicle OBDII port

OEM uConnect module has been removed (JK's only)



JK1001 Installation Checklist (cont)	
Verify Insane NavEngine gets a signal <i>Press NAVI button to load Insane NavEngine. Press on the map button on the left hand side. Does it show your location? (If it is continuously “searching for signal”, check to make sure GPS antenna is plugged into the correct port)</i>	
Insert a CD or DVD and verify playback. (JK1001, FJ1001) <i>If it doesn't go in all the way, check to make sure shipping screws have been removed from the top of the unit</i>	
Verify Radio APP is working <i>If you have poor reception on I/E JK1001 or I/E JK2001, verify that the radio adapter is plugged into the WHITE OEM antenna plug and is connected properly to unit.</i>	
If installing with backup or rock camera, verify it is working properly	
If installing WITHOUT backup camera, verify reverse is working properly <i>Put the vehicle in reverse. If no backup camera, it should do nothing. If you get a “no signal” error on JK1001 or JK2001, disengage the backup wire on main harness</i>	
Verify Torque app data display <i>With the vehicle running, launch the Torque app from the main menu. Click on realtime gauges. Does it display live engine data? If not, refer to the installation manual of your particular unit or reach out to Insane Audio technical support.</i>	

Additional Installation Notes:
